

ISO 9001:2015 & ISO 14001:2015
ISO 14064:2018 & ISO 14067:2018
ISO 27001:2022 & ISO 50001:2018
CERTIFIED MANUFACTURER

UPDATE SEDEX, BSCI, WCA, FSC, REACH & RoHS



Cloth Tape Series

2025

A GLOBALLY ORIENTED MANUFACTURER OF SELF-ADHESIVE TAPE


● Tape's Thickness / Backing Material's

The tape's thickness is the thickness of the base material and




● Adhesive to Steel

When the tape is adhered to stainless steel and it is pulled back at a 180 degree angle, the peeling strength is measured. When the figure is big, the adhesive strength is strong.




● Tensile Strength

This is a measurement of the pulling strength needed to tear the tape. When the figure is big, the strength of the film's base is strong.




● Elongation

This evaluates the tape's capacity to adjust to rounded surfaces when its length is stretched. The figure is indicated as a%. For example, in the case of 50%, 1 m. of tape extends to 1.5 m.



● Structure



Cloth Tape No.OCH Matte Cloth Tape No.MOC




Cloth tape: Strong adhesion. High tensile strength. Widely used for heavy-duty packaging, carpet jointing, book mounting protection.

Matte cloth tape: Matte finish. Good strength and conformability. Non-reflective finish. Tear by hand.

Usage

- Heavy duty packaging.
- Carpet jointing.
- Book mounting protection.
- Working temperature: -10°C~40°C.


Structure



OCH27	OCH35	OCH50	OCH70	OCH90	MOC
Cloth [27mesh]	Cloth [35mesh]	Cloth [50mesh]	Cloth [70mesh]	Cloth [90mesh]	Cloth [70mesh]
Hot Melt					
Black, White, Silver, Red, Yellow, Blue, Green Brown, Dark Brown, Brownish Yellow					Black, Silver Camouflage
≥14					
78	83	100	115	140	≥100
25					≥25
0.170 ±10%	0.175 ±10%	0.190 ±10%	0.205 ±10%	0.220 ±10%	0.210 ~0.450



Pocket Flat Cloth Tape No. POC Cloth Tape Without Core No. CTWC




Pocket flat cloth tape: Strong adhesion, high tensile strength, easy to carry with, widely used when you are working outside.

Cloth tape without core: No core. Strong adhesion. High tensile strength. Easy to carry with, widely used when you are working outside.

Usage

- Flat shape, easy to put into pocket.
- Especially for DIY market.
- Mainly for outworking.

Structure



Transparent Duct Tape No. COC UV Cloth Protection Tape No. BOC Black/White UV Resistant (Double Laminated) Cloth Tape No. DCUT




Transparent duct tape: Terminator of ugly repairs.

UV cloth protection tape: Designed for permanent and temporary applications both indoors and outdoors with high tensile cloth and aggressive adhesive. It offers sunlight/UV resistance and clean removal.

Usage

- For any repair projects in or around the home, vehicle, boat or job site. Marking repairs less noticeable.
- For permanent and temporary applications both indoors and outdoors.

Structure



Performance

Performance											
Items	CTWT	POC27	POC35	POC50	POC70	POC90	COC	BOC	BOC	BOC	DCUT
Backing	Cloth	Cloth [27mesh]	Cloth [35mesh]	Cloth [50mesh]	Cloth [70mesh]	Cloth [90mesh]	Cloth [27mesh]				Cloth [70mesh]
Adhesive	Hot Melt						Acrylic Emulsion Hot Melt	Hot Melt			
Colors.	Color	Black, White, Silver, Red, Yellow, Blue, Green, Brown, Dark Brown, Brownish Yellow					Clear	Blue		Red	White Black
Adhesion To Steel (N/in)	≥ 14						≥ 10	≥ 8	≥ 9.8	≥ 19.6	≥ 9.8
Tensile Strength (N/in)	78-140	78	83	100	115	140	≥ 100		≥ 115		
Elongation (%)	25	≥ 20									
Total Thickness (mm)	(0.155~0.210) ±10%	0.170 ±10%	0.175 ±10%	0.190 ±10%	0.205 ±10%	0.220 ±10%	0.165 ±10%	0.210 ±10%	0.230 ±10%	0.290 ±10%	0.230 ±10%



Gaffer Tape No.GAT Fluorescent Gaffer Tape No.FGAT




Gaffer tape & Fluorescent gaffer tape: Good strength and conformability. It's preferred in many application because of its matte, non-reflective finish. Tear by hand.

Usage

- Matte finish, cloth texture touch feeling.
- Increase grip friction force.

Structure



Heavy-duty Cloth Tape No.HCOT PE-Tarpaulin Repair Tape No.PTRT Luminescent & Fluorescent Cloth Tape No.FLCT



Heavy-duty cloth tape: Heavy-duty, long holding power, hand-tearable, very good strength.


PE-Tarpaulin repair tape: UV resistant up to 3 years, waterproof, and wide temperature range(-40℃ - 80℃) a tough, abrasion resistant backing for repairing job and keep out moisture.

Luminescent & Fluorescent cloth tape: Indoor and outdoor also in sunlight. Bundling, packing, repairing securing masking in heavy-duty areas such as shipbuilding.

Usage

- Heavy duty.
- Long holding power.
- Easy tear by hand.
- Waterproof.
- UV resistant up to 3 years.

Structure



Performance

Items	GAT	FGAT	HCOT	PTRT	FLCT
Backing	Cloth[90mesh]	Cloth	Cloth[50mesh]	PE	Cloth[27mesh]
Adhesive	Hot Melt / Acrylic Emulsion		Hot Melt		
Colors.	White, Black, Red	Yellow, Green, Orange, Pink	Black, Silver	Orange, Dark Green	Green, Yellow
Adhesion To Steel (N/in)	≥ 7.5	≥ 17.5	≥ 9.8	≥ 25	≥ 18
Tensile Strength (N/in)	≥ 225	≥ 225	≥ 110	≥ 350	≥ 95
Elongation (%)	15	≥ 30	≥ 20	≥ 15	≥ 20
Total Thickness (mm)	0.300±10%	0.200±10%	0.250±10%	0.425±10%	0.230±10%



Camouflage Cloth Tape No.CCOT

Fluorescent Cloth Tape No.FCOT

Luminescent Cloth Tape No.LCT



Camouflage cloth tape: Mainly used in military field exercise and police hospitals, it is waterproof. Mainly used in binding air condition pipes, sealing, universal use in first-aid kit.

Fluorescent cloth tape: Consists of a layer of fluorescent material. It can reflect light or absorb and emanate light circularly.


Luminescent cloth tape: Glow in the dark tape. Light yellow color in non-luminance condition, green in luminance condition. High initial luminance, long duration. For safe guiding, place name sign, traffic sign, fire fighting, etc.

Usage

- Good strength and conformability.
- Waterproof.
- Long holding power.
- Easy tear by hand.

- For safe guiding, place name sign, traffic sign, fire fighting, etc.

Structure



Printed Cloth Tape No.PCT

Printed Cloth Tape(Don't hurt Wallpaper) No.PCT-01




Printed cloth tape: Designed for permanent and temporary applications both indoors and outdoors with high tensile cloth and aggressive adhesive. It offers sunlight/UV resistance and clean removal.

Printed cloth tape(don't hurt wall paper): Don't hurt wallpaper formula, especially designed for DIY purpose.

Usage

- It offers sunlight/UV resistance and clean removal.
- Excellent for creative, funny collage.

Structure



Performance

Items	CCOT	FCOT	LCT	PCT	PCT-01
Backing	Cloth [30mesh]	Cloth [27mesh]	0.045mm PE Film +Cloth[32mesh]	Cloth [35mesh]	Cloth [27mesh]
Adhesive	Hot Melt				
Colors.	Color		White	Color	
Adhesion To Steel (N/In)	≥ 12		21.8	≥ 25	≥ 10
Tensile Strength (N/In)	≥ 78		95	≥ 83	
Elongation (%)	≥ 25		28	25	
Total Thickness (mm)	0.170±10%	0.190±10%	0.210±0.010	0.170±10%	



Metallized Cloth Tape No.MCT **Glitter Cloth Tape** No.GCT **Low Temperature Cloth Tape** **No.LOCH**



Metallized cloth tape: Metallized color, strong adhesion, high tensile strength. Widely used for heavy-duty packaging, carpet jointing. Book mounting protection.


Glitter cloth tape: Maintain good water resistance and gloss, excellent for decoration.

Low Temperature Cloth Tape: Can use in range -20 C~ 0 C.

Usage

- Strong adhesion.
- High tensile strength.
- Used for packaging or decoration.

Structure



Performance

Items	MCT	GCT	LOCH
Backing	0.045mm PE Film +Cloth[27mesh]	Glittered PE Film /Textile	Cloth/PE Film
Adhesive	Hot Melt		
Colors.	Silvery White	Glittering Color	Black, Silver
Adhesion To Steel (N/In)	19.6	> 7.92	> 9.8
Tensile Strength (N/In)	89	> 98	> 95
Elongation (%)	18	> 20	> 25
Total Thickness (mm)	0.170 ±10%	0.235 ±10%	0.170~0.230

