ISO 9001:2015 & ISO 14001:2015 ISO 14064:2018 & ISO 14067:2018 ISO 27001:2022 & ISO 50001:2018 CERTIFIED MANUFACTURER

UPDATE SEDEX, BSCI, WCA, FSC, REACH & RoHS





Bopp Packaging **Tape Series**

2025


● Tape's Thickness / Backing Material's

The tape's thickness is the thickness of the base material and Tape's Total Thickness Total Thickness.

In product comparisons, Backing Material's the thicker products have stronger stetchability.

Adhesive to Steel


When the tape is adhered to stainless steel and it is pulled back at a 180 degree angle, the peeling strength is measured. When the figure is big, the adhesive strength is strong.



(The catalogue shows the figure measured at 180 degrees.)


Tensile Strength

This is a measurement of the pulling strength needed to tear the tape. When the figure is big, the stregth of the film's base is strong.




Elongation

This evaluates the tape's capacity to adjust to rounded surfaces when its length is stretched. The figure is indicated as a%. For example, in the case of 50%. 1 m, of tape extends to 1.5 m.



Structure



General BOPP Packaging Tape



Bopp packaging tape(OP)/Super clear Bopp packaging tape(CC): Bopp packaging tape features bi-oriented polypropylene film backing and pressuresensitive acrylic emulsion adhesive.

Color Bopp packaging tape(COP): Color Bopp packaging tape is your sorting helping hand in your job.

Printed Bopp packaging tape(OR, SR): Printed tape is an efficient general advertising tool which help your company to stick out in the market, and a kind of security tape with easy-to-recongrise message indicating features to deflect pilferage & counterfeiting.

ge

- Structure
- Packaging carton boxes with automatic sealing machine.
- Packaging for export.
- Steadying & bundling.
- Protection.



Performance	
Items	OP/CC/COP/OR,SR
Backing	BOPP
Adhesive	Acrylic Emulsion Based Adhesive
Colors.	Clear, Brown, Dark Brown(OP)/Super Clear(CC)/ Color(COP)/Customized Design(OR, SR)
Adhesion To Steel (N/In)	3.5~15
Tensile Strength (N/In)	64~186
Elongation (%)	120
Total Thickness (mm)	0.040~0.095







Specialty BOPP Packaging Tape



Low noise Bopp packaging tape(OL)/No noise Bopp packaging tape(ON): Keep your working environment comfortable and free of noise, and work efficiently to save your precious time.

No cutter Bopp packaging tape(NC): No cutter needed work efficiently to save your precious time. Cold-resistant Bopp packaging tape(CRP): A very broad temperature application range that is especially useful when taping in very cold environment. U.V.Resistant Bopp packaging tape(UVP): Special formula is ultraviolet resistant to reduce

yellowing, and aging dry-out. Super clear low noise easy tear packaging tape(SCLE): Keep your working environment comfortable and free of noise, and work efficiently to save your precious time.

Usage

Chrysture

- Packaging efficiently in peaceful environment.
- Packaging carton boxes with automatic sealing machine.
- Packaging for export.Steadying & bundling.



tems	OL/ON/NC/CRP/UVP/SCLE
lacking	BOPP
Adhesive	Acrylic Emulsion Based Adhesive
Colors.	Clear, Brown, Dark Brown(OL, ON, NC) White(CRP)/Red(UVP)
dhesion o Steel (N/In)	3.5~15(CRP:≥12, UVP:≥14)
ensile Strength (N/In)	64~186 (NC:N/A, CRP: ≥ 160, UVP: ≥ 130)
longation (%)	120 (NC:N/A, CRP: ≥ 160, UVP: ≥ 150)
otal Thickness (mm)	0.050~0.090 (CRP:0.097±0.003, UVP:0.075±0.003)
emperature Resistant	





