

*ISO 9001:2015 & ISO 14001:2015
ISO 14064:2018 & ISO 14067:2018
ISO 27001:2022 & ISO 50001:2018
CERTIFIED MANUFACTURER*

UPDATE SEDEX, BSCI, WCA, FSC, REACH & RoHS



Double Sided Tape Series

2025

A GLOBALLY ORIENTED MANUFACTURER OF SELF-ADHESIVE TAPE

Double Sided Crepe Tape

No. DSCT-01, DSCT-02

Double Sided Cloth Tape

No. DOC, DOCH, DOCT




Double sided crepe tape: Strong adhesion. Double-stick. Hand-tearable. (DSCT-01: Used in plastic rigid pvc flooring and concrete floor no glue residue. /DSCT-02: Applied to the golf stick winding.)

Double sided cloth tape: Strong adhesion. Double stick. Hand-tearable.

Usage

- Adhere posters, photos, public notes, envelopes.
- Decoration.
- Fixing of ornament, hook or sign board.
- For laminating nameplate.

Structure



Double Sided PP Tape No. DPP

Double Sided PET Tape No. DPT

Double Sided PE Tape No. DSPE

Double Sided PVC Tape No. DSPT



Double sided PP tape & Double sided PET tape: Excellent quick double stick, strong adhesion, strong tensile strength.


Double sided PE tape: Double sides coated tape with light adhesion on one side, strong on the other.

Double sided PVC tape: The thin and flexible PVC base material strengthens the connection ability of the tape to the curved surface and rough surface. Its excellent temperature resistance, moisture resistance and UV resistance make it widely used in the traditional die-cutting industry.

Usage

- Adhere posters, photos, public notes, envelopes.
- Decoration.
- Fixing of ornament, hook or sign board.
- For laminating nameplate.
- Shoe & leather industry.
- For computerized embroidery.

Structure



Performance

Items	DSCT-01	DSCT-02	DOC	DOCH	DOCT	DPP	DPT	DSPE	DSPT
Backing	Crepe Paper		Cloth[35mesh]		Cloth [90mesh]	PP	PET	PE	PVC
Adhesive	Hot Melt		Acrylic Emulsion	Hot Melt		Acrylic Solvent		Acrylic Emulsion	Acrylic
Colors.	White	Tan	White, Yellow		White	White, Yellow		White, Clear	White, Yellow
Adhesion To Steel (N/in)	A Side:14.7 B Side:20	A Side:14.7 B Side:14.7	A Side:9.8~20	B Side:20	A Side:49 B Side:28	A Side:11	B Side:11	A Side:≥6.3 B Side:≥30	A Side:≥18 B Side:≥15
Tensile Strength (N/in)	79		49-98		≥130	90		39	≥100
Elongation (%)	15-20		N/A		13	120	100	200	≥15
Total Thickness (mm)	0.280±10%	0.260±10%	0.240±10%	0.230±10%	0.485±10%	0.180~0.220		0.180~0.230	0.250±10%



Duo PE Tape No.D/S PENW
Duo WARIFU Tape No.DPE
Double Sided WARIFU Tape
No.WARIFU



Duo PE tape: Double sides coated tape with light adhesion on one side, strong on the other.


Duo WARIFU tape: High tack. Double-stick. Strong tensile strength.

Double sided WARIFU tape: High tack. Double-stick. Strong tensile strength.


Usage

- Insulation sealing of connection of wire and cable.
- For pipeline protection, remedy and sealing.

Structure



Double Sided Tissue Tape No.SD-01
Transfer Tape No.TTP, TTF-02
Double Sided Heat Embroidery Tape No.DSHT



Double sided tissue tape: Excellent quick double-stick. Strong adhesion. Tear by hand.


Transfer tape: Excellent quick double-stick. Strong adhesion.

Double sided embroidery tape: Specially designed for embroidery job, become sticky by heat.

Usage

- For various pipe wrapping.
- For industrial use.

Structure



Performance

Items	D/S PENW	DPE	WARIFU	SD-01	TTP	TTF-02	DSHT
Backing	PE	1-layer PE	3-layer PE	Tissue	Release Paper		
Adhesive	Acrylic Emulsion / Hot Melt		Acrylic Emulsion	Acrylic Emulsion Acrylic Solvent Hot Melt	Hot Melt	Acrylic Emulsion	Hot Melt
Colors.	White, Clear		Brown	White, Yellow	Clear		
Adhesion To Steel (N/In)	A Side:8.8 B Side:20	A Side:9.8 B Side:20	A Side:24 B Side:24	A Side:11-25 B Side:11-25	A Side:11 B Side:11	A Side:~5 B Side:~5	9.8
Tensile Strength (N/In)	15	≥86	≥200	30		N/A	
Elongation (%)	200	30	12	3		N/A	
Total Thickness (mm)	0.220±0.020	0.380±0.020	0.475±10%	0.180~0.220	0.230±10%	0.105~0.130	0.220±0.009



Double Sided Foam Tape No.SF-01

Weather-Strip Foam Tape No.DSS, SSS

Duo Tape No.DUO

Mosaic Double-Sided Tape No.MDST



Double sided foam tape: Excellent shock resistance. Designed for rough surfaces with heat insulation. Mainly for hook, nameplate, poster, panels, etc. It can be die-cutted into various shapes.

Weather-strip foam tape: Good draught excluder for doors and windows, provides good heat and sound insulation, protects against the cold, wind, dust and rain.


Duo tape: Easy & fast for masking application.

Mosaic double-sided tape: For DIY market. Stick mosaic to wall.

Usage

- For mounting decorative objects in cars machines or houses.
- Applicable for permanent fixing.
- Auto doors and trunks.
- For irregular surface.
- Marine hatches. Deck lids.

Structure



Double Sided Stick Tape No.DST, DST-01

Double Sided Acrylic Foam Tape No.DSAF

Double Sided Craft Tape No.DSC

Weather Sealing Tape No.EPDM



Double sided stick tape: No glue residue(DST). Great for crafts, mounting, eco-friendly, no release liner.

Double sided acrylic foam tape: Translucent resistance to abrasion, corrosion and moisture for. Metal stiffener bonding. Trim attachment electronic parts, etc.


Double sided craft tape: Excellent adhesion and holding power. Used for circuitry insulation and adherence.

Weather sealing tape: All climate EPDM rubber weather seal for gaps seal out drafts and dust around doors and windows.

Usage

- For light duty attaching and mounting, sealing, wrapping & crafts.
- Securely mount posters or light weight objects on doors, walls, tile, glass, vinyl, wall papers, etc. Removes without damage.

Structure



Performance											
Items	SF-01	DSS	SSS	DUO	MDST	DST	DST-01	DSAF	DSC	EPDM	
Backing	PE or EVA Foam	Alternative		PVC	N/A	PET	0.025mm PET	Foam	PET	EPDM	
Adhesive		Acrylic		Acrylic Emulsion	Hot Melt	Acrylic Emulsion	Acrylic Emulsion Hot Melt	Acrylic	Hot Melt	Acrylic Solvent	
Colors.		White, Black		White Green	White	Clear		Super Clear	Clear	Grey White	
Adhesion To Steel (N/in)		A Side:12	B Side:12	A Side:6.5 B Side:12	>35.2	A Side:2.45 B Side:1.47	A Side:7.3 B Side:2.0	A Side:25 B Side:25	A Side:14.7 B Side:19.6	A Side:11.76 B Side:11.76	
Tensile Strength (N/in)	25	N/A		>79	41	>98	>88	>128	>98	>330	
Elongation (%)	EVA:100~150 PE:200~350	N/A		>260	950	>100		>880	>100	>300	
Total Thickness (mm)	1.0~2.0	5~10		0.270 ±10%	1.420 ~1.450	0.085±0.005		1-5	0.280 ±10%	6	



Construction Tape No.COT

No Sewing Double Sided Opp Tape

No.NSDOT




Construction tape: Construction tape with an extremely high initial bond strength, for internal and external applications. Fixing without nails or screws. Extreme grip.

No sewing double sided opp tape: Hem your pants in seconds-No sewing! Attach this no-iron tape to the inside of your pant leg, fold it up to the designed, length, and then press firmly. Instant hem! Easy to remove and leaves no residue.

Usage

- For internal and external applications.
- Fixing without nails or screws.
- Extreme grip.
- Easy to remove and leaves no residue.

Structure



Performance

Items	COT	NSDOT	
Backing	Cloth	OPP	
Adhesive	Hot Melt	Acrylic Oil Based	
Colors.	Clear	White	
Adhesion To Steel (N/in)	>65	>24.5	
Tensile Strength (N/in)	>60	>98	
Elongation (%)	>450	>100	
Total Thickness (mm)	0.800±10%	0.300±10%	

