

*ISO 9001:2015 & ISO 14001:2015  
ISO 14064:2018 & ISO 14067:2018  
ISO 27001:2022 & ISO 50001:2018  
CERTIFIED MANUFACTURER*

*UPDATE SEDEX, BSCI, WCA, FSC, REACH & RoHS*




# Duct Tape Series

# 2025

A GLOBALLY ORIENTED MANUFACTURER OF SELF-ADHESIVE TAPE

# PVC Duct(Wrapping) Tape No.PD PVC Embossed Tape No.PW PE Embossed Tape No.PEE




**PVC duct(wrapping) tape & PVC embossed tape & PE embossed tape:** Ideal for underground pipeline or conduit's corrosion & abrasion protection. Good resistance to moisture, humidity, corrosion and temperature variations.

## Usage

- For various pipe wrapping.
- For industrial use.

## Structure




## Performance

Items	PD	PW
Backing	Gloss PVC Film	Embossed PVC Film
Adhesive	Rubber Based	
Colors.	Silver, Black	Silver, Black, Blue White, Red, Yellow, Tan
Adhesion To Steel (N/in)	$\geq 3.8$	$> 4$
Tensile Strength (N/in)	$\geq 49$	
Elongation (%)	$\geq 150$	$> 100$
Total Thickness (mm)	0.130 $\pm 10\%$	0.170 $\pm 10\%$



## ● Tape's Thickness / Backing Material's

The tape's thickness is the thickness of the base material and



the self-adhesive. In product comparisons, the thicker products have stronger stretchability.

## ● Adhesive to Steel


When the tape is adhered to stainless steel and it is pulled back at a 180 degree angle, the peeling strength is measured. When the figure is big, the adhesive strength is strong.



(The catalogue shows the figure measured at 180 degrees.)


## ● Tensile Strength

This is a measurement of the pulling strength needed to tear the tape. When the figure is big, the strength of the film's base is strong.



## ● Elongation

This evaluates the tape's capacity to adjust to rounded surfaces when its length is stretched. The figure is indicated as a%. For example, in the case of 50%, 1 m. of tape extends to 1.5 m.



## ● Structure

