

*ISO 9001:2015 & ISO 14001:2015  
ISO 14064:2018 & ISO 14067:2018  
ISO 27001:2022 & ISO 50001:2018  
CERTIFIED MANUFACTURER*

*UPDATE SEDEX, BSCI, WCA, FSC, REACH & RoHS*




# Specialty Tape Series

# 2025

A GLOBALLY ORIENTED MANUFACTURER OF SELF-ADHESIVE TAPE

### ● Tape's Thickness / Backing Material's

The tape's thickness is the thickness of the base material and



the self-adhesive. In product comparisons, the thicker products have stronger stretchability.

### ● Adhesive to Steel


When the tape is adhered to stainless steel and it is pulled back at a 180 degree angle, the peeling strength is measured. When the figure is big, the adhesive strength is strong.



(The catalogue shows the figure measured at 180 degrees.)


### ● Tensile Strength

This is a measurement of the pulling strength needed to tear the tape. When the figure is big, the strength of the film's base is strong.




### ● Elongation


This evaluates the tape's capacity to adjust to rounded surfaces when its length is stretched. The figure is indicated as a%. For example, in the case of 50%, 1 m. of tape extends to 1.5 m.



### ● Structure



## Toffee Tape No.TF Pastilles Adhesive Tape No.PAAT




**Toffee tape:** Laminating carpet's aluminum foil to floor.

**Pastilles adhesive tape:** Removable adhesive pegging small items. No glue residue or damage on most surface mainly for photo's fix-up.

#### Usage

- Laminating carpet's aluminum foil to floor.
- Removable adhesive pegging small items.
- No glue residue or damage on most surface mainly for photo's fix-up.

#### Structure



#### Performance

Items	TF	PAAT
Backing	Hot-Melt Glue	N/A
Adhesive	Hot Melt	
Colors.	Clear Yellowish	White, Brown Blue, Yellow
Adhesion To Steel (N/in)	0.98	
Tensile Strength (N/in)	N/A	
Elongation (%)	N/A	
Total Thickness (mm)	1.000±10%	2.500±10%



# Stretch Wrap Film No.PT01, PT02

## MOPP Strapping Tape

### No.MOS, MOS-02

## Easy Cleaning Tape No.EC



**Stretch wrap film:** Excellent puncture and tear resistance. Good shrink-to-original size for an extremely tight. (PT01: For hand application. /PT02: For machine application)


**MOPP strapping tape:** Good for bundling and tying various plastic bags using in bag neck sealer.

**Easy cleaning tape:** Handy & easy to use. Convenient and practical tool to clean dust from clothes, car seats, desk tops.

#### Usage

- Used on (small) cracks in plaster walls, without plastering after it, also possible to paint it.
- Wall must be clean and dry.
- Failure to completely fill the joint may result in cracking.
- For best result, use a setting-type compound.

#### Structure



#### Performance

Items	PT01	PT02	MOS	MOS-02	EC	ST
Backing		LLDPE		MOPP	Crepe Paper	TEFLON
Adhesive		Cling		Hot Melt	Acrylic Solvent	N/A
Colors.		Clear	Red	Blue	Natural Color	White, Yellow
Adhesion To Steel (N/in)		N/A	11	≥ 8.3	8	N/A
Tensile Strength (N/in)		N/A	245	≥ 294		N/A
Elongation (%)		300	150	≥ 60		N/A
Total Thickness (mm)		0.015~0.025	0.110	0.080±10%	0.120±10%	Alternative

# PTFE Thread Sealing Tape No.ST




**PTFE thread sealing tape:** Acid and alkali resistant, excellent insulation of high and low temperature. Widely used in sealing and locking the threads of water, air and oil conduit.

#### Usage

- Sealing & locking thread.
- Used in pressurizing the screws of oil, water and air conduits.
- Acid & alkali resistant.
- Insulation of temperature.
- Soft, flexible.

#### Structure



## Corner Sealing Tape No. CST Corner Masking Tape No. CMST



**Corner sealing tape:** Seal gaps between bathtub and walls. It's flexible and conformable.

**Corner masking tape:** Corner masking tape has a pair of perfectly parallel thin metallized tapes into which you apply your silicone. Specially designed for the application of perfect silicone joints.

## Hook & Loop Fastening Tape No. NF-1, NF-2




**Hook & loop fastening tape:** High performance hook and loop backing. Strong adhesion and no adhesion residue.

### Usage

- Seal gaps between bathtub and walls.
- Simple preparation and easy removal.
- Ideal for Benchtops, Kitchens, Laundry, Bathtubs & Spas.


### Structure



### Usage

- Mounting propagandes material in exhibition.
- Positioning of office supplies, household commodities.
- Fastening of car accessories.

### Structure




### Performance

Items	CST	CMST	NF-1	NF-2
Backing	PVC+PE Foam PE Film	PET		Nylon
Adhesive	Acrylic Solvent	Acrylic Emulsion		Rubber
Colors.	White/Red	Silver		White,Black
Adhesion To Steel (N/in)	11.76	5.88-17.6		29
Tensile Strength (N/in)	> 490	19.6		490
Elongation (%)	N/A	200		N/A
Total Thickness (mm)	2.100±10%	0.070		Alternative



## Premium Clear Tape No. PRCT Light Weight Heat N Bond No. LWHB Tubular Tape No. TUT



**Premium tape:** Satin-like surface, good for office, home and school application.


**Light weight heat N bond:** Specially formulated for embroidery field. Needles won't gum up.

**Tubular tape:** Strong adhesion. For tubular tire & tubular rim only.


### Usage

- Protection.
- Packing. Good for office, home and school.
- Specialty formulated for embroidery field.
- For tubular tire & tubular rim.

### Graphic



## Micro-Pore Tape No. MPT Frozen Tape No. FRT




**Micro-pore tape:** Used for dust protection in refrigerator compressor, breathable film, let some air in and stop dust.

**Frozen tape:** Bundled PU foam insulation material. Used in low temperature environments.

### Usage

- Used for dust protection in refrigerator compressor.
- Bundled PU foam insulation material.
- Used in low temperature environments.

### Structure




### Performance

Items	PRCT	LWHB	TUT	MPT	FRT
Backing	OPP	Release Paper	PET Non-Woven	Tissue	PE
Adhesive	Acrylic Emulsion	Hot Melt	Acrylic Solvent	Acrylic Emulsion	
Colors.	Super Clear	Clear	Black	White	
Adhesion To Steel (N/in)	> 3.92	N/A	> 24.5	0.49	15.68
Tensile Strength (N/in)	> 80	N/A	> 65	17.5	27
Elongation (%)	> 120	N/A	> 50	10	450
Total Thickness (mm)	0.055±0.002	0.110±10%	0.400±10%	0.120±10%	0.085±0.003



## PE Sealing Tape No.PST Grafting Belt No.GBT



**PE sealing tape:** Waterproof, flexible in moderate freezer and withstand intermittent exposure to 90 °C, an ideal sealing tape for petri dishes.

**Grafting belt:** When exposed to sunlight for 5 / 6 months, it will decompose itself. Used for grafting plant.

## Plant Wrap Tape No.PLWT




**Plant wrap tape:** Excellent stretchability. It sticks to itself when stretched. Does not stick to your fingers. Smooth surface ensures a smooth, clean and bright finish to enhance appearance, particularly for weddings.

### Usage

- Waterproof.
- For petri dishes.
- Suitable for the fixed binding of trees and plants. Used to bundle rattan and Vine in gardens and farms, or bundle vegetables in supermarkets.

### Structure



### Usage


- Various sizes.
- High tensile strength at break.
- Used for plant bundling.
- Non-toxic and environmentally friendly.

### Structure



### Performance

Items	PST	GBT	PLWT
Backing	PE	PE	N/A
Adhesive	Acrylic Emulsion	N/A	PP
Colors.	Red	Transparent Green	Emerald, White
Adhesion To Steel (N/in)	> 7	N/A	N/A
Tensile Strength (N/in)	> 45	> 78	> 9.8
Elongation (%)	> 300	> 500	> 450
Total Thickness (mm)	0.135±10%	0.150±10%	0.140-0.160



## Grass Protection Sheet Tape No. GPST



**Grass protection sheet tape:** Specially designed to suppress grass growth. With liner or without liner.

### Usage

- Specially designed to suppress grass growth. With liner or without liner.

### Graphic



## PE Hot-Sensitive Tape No. PEPT Magnetic Tape No. MAT




**PE hot-sensitive tape:** With the use of adhesive such as iron high temperature hot pressing to the canvas.

**Magnetic tape:** Good for shelf labeling. Magnetic rolls with an adhesive on one side. Adhere to anything you want to put on a magnetic surface. Attach to light-weight pictures, business cards, and much more.

### Usage

- Applicable to garment manufacturing industry.
- Good for shelf labeling.
- Attach to light-weight pictures, business cards, and much more.

### Structure



### Performance

Items	GPST	PEPT	MAT
Backing	PE Non-Woven	PE	Magnetic Rubber
Adhesive	Acrylic Emulsion	Hot Melt	Rubber
Colors	Black	Yellowish	Dark Brown
Adhesion To Steel (N/in)	> 25	N/A	> 2.94
Tensile Strength (N/in)	> 98	> 19.6	> 80
Elongation (%)	15-20	N/A	> 150
Total Thickness (mm)	0.200±10%	0.170±10%	0.300-0.500

