

*ISO 9001:2015 & ISO 14001:2015  
ISO 14064:2018 & ISO 14067:2018  
ISO 27001:2022 & ISO 50001:2018  
CERTIFIED MANUFACTURER*

*UPDATE SEDEX, BSCI, WCA, FSC, REACH & RoHS*




# Surface Protection Tape Series

# 2024

A GLOBALLY ORIENTED MANUFACTURER OF SELF-ADHESIVE TAPE

## Carpet Protection Tape No.PCP, CCP Felt Tape No.KL



**Carpet protection tape:** Protects carpets from job site dirt and grime. Keep carpet clean while working and protect carpet from damage while moving.

**Felt Tape:** Ultra heavy-duty. Self-stick. Strong adhesion. Excellent non-slip properties. Prevent scratching and noise. Good for chairs, table's legs, stools.

## PE Protection Tape No.PP-02, PP-03 PVC Protection Tape No.PC-01, PC-02




**PE protection tape:** Excellent protection against damages and scratches from transportation and removal and production for a wide range of application.

**PVC protection tape:** For aluminium material, door and window's protection during transportation.

### Usage

- Can be used to protect counters, table and anywhere to save time, save money and reduce cleanup cost .
- Used on chairs stools, table's legs.
- Used on stereos, clocks, stoves TVS, refrigerators.


### Structure



### Usage

- Aluminium material.
- Used for protection door, windows and floor.
- For electronic circuit board protection while welding.

### Structure




### Performance

Items	PCP	CCP	PP-02	PP-03	PC-01	PC-02	KL
Backing	PE Film	Crepe Paper	PE		PVC		Felt
Adhesive	Acrylic Emulsion		Acrylic Emulsion/Acrylic Solvent		Acrylic Solvent		
Colors.	Clear, Customized Printing	Customized Printing	Transparent-Blue	Black/White	White, Transparent-Blue	Dark Blue	Black, Grey
Adhesion To Steel (N/In)	≥ 4.9	≥ 1.9	0.9~1.9	1.6~2.4	1.79	1	14.2
Tensile Strength (N/In)	≥ 45	≥ 75	25	35~58	50	45	N/A
Elongation (%)	≥ 300	≥ 18	160	600~800	150	150	N/A
Total Thickness (mm)	0.060~0.080	0.120±10%	0.060~0.120	0.080~0.100	0.115±10%	0.085±10%	3~6



**Laser Protection Tape No.LAP**  
**Decoration Window Film No.DWF**  
**OPP Lens Tape No.OPLS, OPLI**



**Laser protection tape:** Excellent protection against damages and scratches from transportation.


**Decoration window film:** Modern art look glasses door and windows make a colorful statement. Different season has different decoration. Installation is simple and it's very easy to work with.

**OPP lens tape:** Good for fancy gift packing and decoration.

**Usage**

- Decoration.
- Gift wrapping.
- Excellent protection against damages.

**Structure**



**Door Seal Tape No.DOS**  
**Floor Seal Tape No.FLSG**  
**No Residue Floor Seal Tape No.FLSN**



**Door seal tape:** 14 days no glue residue on the door frame.


**Floor seal tape:** Permanent adhesive formula to ensure sticking firmly.

**No residue floor seal tape:** 14 days no glue residue on the floor.

**Usage**

- Protection.
- Keep things clean outside the workplace.
- Auxiliary Flooring. Fixed.

**Structure**



Performance							
Items	LAP	DWF	OPLS	OPLI	DOS	FLSG	FLSN
Backing	PP	PE	CPP & Aluminized		PE		
Adhesive	Acrylic Emulsion	N/A	Acrylic Emulsion		Acrylic Emulsion		
Colors.	Color	Frosted Printed-Embossed	Color		Lime Green /Blue/Clear	Clear	
Adhesion To Steel (N/In)	≥ 1.76	N/A	≥ 5.8		≥ 7.0	≥ 8.0	≥ 7.0
Tensile Strength (N/In)	≥ 79	N/A	≥ 34		≥ 35	≥ 64	
Elongation (%)	≥ 120	N/A	≥ 250		≥ 700	≥ 800	
Total Thickness (mm)	0.045±0.002	0.10-0.12	0.100		0.090-0.110	0.168±0.005	

